

Dawnprene TPV 21-73A

TPV

TPV

Features:

A soft, natural thermoplastic vulcanizate (TPV) in the thermoplastic elastomer (TPE) family. This material combines good physical properties, chemical resistance and elasticity, designed for extrusion and injection applications. This grade of TPV can be processed on conventional thermoplastics equipment for extrusion, injection molding. It is polyolefin based and completely recyclable.

RoHS	RoHS		
	2019-5-16		
	0.917	g/cm ³	ASTM D792
70 *24 7KPA		—	—
(Shore A, 10 sec, 23)	72.3	A	ASTM D2240
100% - 23	3.13	Mpa	ASTM D412
- 23	7.31	Mpa	ASTM D412
- 23	570	%	ASTM D412
- 23 Die C	33.2	KN/m	ASTM D624
23 , 70hr, 1 B	33	%	ASTM D395
70 , 22hr, 1 B	38	%	
100 , 22hr, 1 B	58	%	
	-55		ASTM D746
	-40 105		
	-60 125		
(23)	2.65		ASTM D150
	35	mm/min	GB/T8410
(125 , 168hr)	-12	%	ASTM D573
(125 , 168hr)	-18	%	
(125 , 168hr)	-2	A	
(125 , 168hr)	-1.5	%	

Tel:(Foreign Trade) 0086-535-8868588;(Domestic Trade)0086-535-8833988