

TPO

TPO

Features: It is a natural colour thermoplastic polyolefin (TPO) material. This material combines good physical properties, chemical resistance and elasticity, designed for extrusion applications. This grade of TPO can be processed on conventional thermoplastics equipment for extrusion. It is completely recyclable.

RoHS	RoHS		
	2022-03-30		
	1.09	g/cm ³	GB/T 1033.1-2008
(Shore A/D,10/1 sec,23 °C)	94/40	A/D	GB/T 531.1-2008
230 *5kg	2.0	g/10min	GB/T 3682-2000
/ 23	15/16	Mpa	GB/T 528-2009
/ 23	780/785	%	GB/T 528-2009
/ 23	63/66	KN/m	GB/T 529-2008



R							
4	16-170	180-210	180-210	180-210	180-210	180-210	50-70

1. Do not mix nprene TPO with PVC

Do not mix nprene TPO with PVC materials, hence must clean the equipment before using.

2.

The properties is typical performance, is not regarding as technical index or agreement.

3.

Any reprocessing must follow the above instructions, and ensure no content impurity.

4.

Above instructions for reference only, different equipment might have difference parameters, please adjust accordingly with different mold and product shape.

SHANDONG DAWN POLYMER CO.,LTD

:

. 265703

Address: Zhenxing Road, Longgang Economic Zone, Longkou, Shandong, China. 265703

() 0086-535-8868588;()0086-535-8833988

Tel:(Foreign Trade) 0086-535-8868588;(Domestic Trade)0086-535-8833988